Technical Datasheet

40W LED Downlight Round - Philips CertaDrive - CCT -UGR13 - IP65



Product code:

Reference: 90722

Technical specifications:

REFERENCE: 90722 Rated Power: 40w Nominal Voltage: 175-265V Colour: SELECTABLE COLOUR: 3000K-4000K-6000K CRI - Chromatic Rendiment Index: 85 Construction Material: Aluminiun+PC Luminosity-Lm: 5000 Number & Type of LEDs: COB Bridgelux Beam Angle (^o): 45^o Luminous diodo LED (Lm/W): 150Lm/W Luminous Efficiency (Lm/W): 125 Lm/W Certifications: CE - ROHS IP : Front: IP65 - Philipsd CertaDrive: IP20 Diode Life Expectancy (H): 40.000 Dimensions (mm): Ø165mm * H115mm Power Factor (PF): 0,95 Frequency (Hz): 50/60Hz Temperature Range ($^{\circ}C$): -20°C ~ +55°C On/Off Cycles: 100.000 Starting Time (s): 0,2s Cut-out Size (mm): Ø145mm Glare Rating (UGR): 13 Driver included: PHILIPS CertaDrive Energy Rating (2021-UE-2019/2015): A+ Energy Rating (2023 - UE-2019/2015): F Warranty Years: 3

Product short description:

DOWNLIGHT CCT: SELECTABLE COLOR: Our **40W Philips CertaDrive** circular recessed LED Downlight has a color temperature selector, cool white, neutral white and warm white. UGR13. Angle of 120^o. The front of the luminaire is **IP65.**

Product description:

40W LED Downlight - Philips CertaDrive- CCT - UGR13 - Special for Bathrooms and Kitchens - Front IP65 - Circular

Our Philips CertaDrive Downlight with 40W power is characterized by its easy handling, achieving precise and personalized lighting in any interior and exterior space.

In addition, with its high UGR you will not have problems with glare, since it has a low glare index UGR13.

SELECTABLE COLOR: Our Downlight has a color temperature selector, being able to choose between cold white - 6000K-, neutral white -4000K- and warm white -3000K-.

Thanks to its color selection system you can adapt it to the needs of your business or your home, being able to choose the desired color for each room or room.

The high-efficiency BRIDGELUX light source delivers high luminosity, which will perfectly replace traditional spotlights, providing savings of over 80%.

With its functional design, installation is quick and easy.

Its high color rendering index +85 guarantees natural color reproduction.

Its aluminum body is specifically designed so that the temperature of the LED is optimal and achieve the best performance and durability.

The front part of the luminaire is IP65 so it can also be used in humid areas such as bathrooms and in indoor outdoor areas. the Philips CERTADRIVE power supply is IP20. Its reflector, made of technical PMMA, creates a high-quality, uniform and spot-free light.

Uses: 40W LED Downlight - Philips CertaDrive- CCT - UGR13 - IP65 - Circular

StoresRestaurants

Technical Datasheet

- Museums Commercial galleries Malls •
- - Malls Toilets Kitchens Indoor outdoor corridors Shop windows
- .

At FactorLED we ensure that our products have a QUALITY guarantee and offer all the necessary elements for DISTRIBUTION, IMPORT or WHOLESALE, including the technical sheet of each LED product.

Additional images:



















