## Dimmable Driver DALI 2 - PUSH - 25W - 42W BOKE | 3v-42v | 600mA-1100mA | IP20



## **Product code:**

Reference: PUL42W

## **Technical specifications:**

REFERENCE: PUL42W Rated Power: 42W

Nominal Voltage: 600-1100mA - 3v-42v

Dimmable: DALI 1-100%

Certifications: CE-RoSH-TÜV-ENEC

IP: IP20

Diode Life Expectancy (H): 100.000 Dimensions (mm): L103 x W68 x H60mm

Frequency (Hz): 50/60Hz

Temperature Range ( ${}^{\circ}$ C): -20 ${}^{\circ}$ C ~ +45 ${}^{\circ}$ C

Warranty Years: 5

#### **Product short description:**

Dimmable DALI multicurrent driver 42w. Dimming with DALI protocol. Constant current output, for LED luminaires of 3-42V and intensity between 600ma and 1100ma. The driver incorporates EMC filter, does not produce flicker (NO FLICKER) and regulates in a fluid and constant way the lighting without jumps and without noise.

## **Product description:**

DALI dimmable driver 42W | 3v-42v | 600mA-1100mA | IP20

Multi-current dimmable DALI driver 42w. Dimming with DALI protocol. Constant current output, for LED luminaires of 3-42V and intensity between 600ma and 1100ma. The driver incorporates EMC filter, does not produce flicker (NO FLICKER) and regulates in a fluid and constant way the lighting without jumps and without noise.

The DALI dimming and is specially designed for dimmable LED lighting with uniform, flicker-free, smooth and noise-free dimming


- INPUT: 200-240VAC ~ 50/60Hz 0.3A
- OUTPUT: 50V Max.

### **Additional images:**













# **Technical Datasheet**





