

## LED Tracklight 40W - 34W - NEW MAYA - White- 3-PHASE Rails - CRI+92 - UGR13 - HIGH LUMEN 140Lm/W



### Product code:

Reference: TL40W-NEWMAYA

### Technical specifications:

REFERENCE: TL40W-FARUM  
Rated Power : 40w  
Nominal Voltage: 85V-265V  
Colour: 3000K - 4000K  
CRI - Chromatic Rendiment Index: 92  
Construction Material: Aluminium +PMMA  
Luminosity-Lm: 5600  
Number & Type of LEDs: COB BRIDGELUX 130 CHIP 2630 DS-C30  
Beam Angle (°): Interchangeable angels: 24° - 60°  
Luminous diodo LED (Lm/W): 160 Lm/w  
Luminous Efficiency (Lm/W): 140 Lm/W  
Certifications: CE - ROHS  
Diode Life Expectancy (H): 30.000  
Dimensions (mm): 160x80x156 mm  
Power Factor (PF): 0.91  
Frequency (Hz): 50/60Hz  
Temperature Range (°C): 25°C ~ 45°C  
On/Off Cycles: 100.000  
Starting Time (s): 0,2s  
Glare Rating (UGR): 13  
Driver included: Driver No Flick  
Energy Rating (2021-UE-2019/2015): A++  
Energy Rating (2023 - UE-2019/2015): D  
Warranty Years: 5

### Product short description:

NEW MAYA LED track spotlight with adjustable power 40W-38W-36W-34W. With professional colour rendering index +98 - Professional and real colours -. It has 2 interchangeable light angles - 24° and 60° -. This makes this spotlight perfect for highlighting specific elements, thus creating multiple atmospheres. It does not produce glare UGR13.

### Product description:

LED Tracklight 40W - 34W - NEW MAYA - White- 3-PHASE Rails - CRI+92 - UGR13 - HIGH LUMEN 140Lm/W

This is one of the most flexible spotlights when it comes to decorating your business, due to its design it allows us to turn it almost completely, light weight but versatile, we get incredible results in the decoration.

This spotlight has a latest generation hemispherical collimating lens (concentrator of light beams) made of PMMA (poly methyl methacrylate) and a curved reflector made of polished aluminium specular in rhombuses, causing a base light and a more concentrated angle to emphasize the object to be illuminated without causing shadows so accentuated with a primary angle of 24° and a secondary angle of 60°.

The projector for commercial use also incorporates a 60° reflector with which a wider beam opening angle can be achieved, which is particularly suitable for areas with lower ceilings or where a larger object is to be highlighted.

High CRI level: Our project stands out for its very high level of colour rendering index, which makes the colours look sharp and real.

The spotlight comes programmed with 40w, although by opening the cover of the -driver- you can change its power by adjusting the output milliamps, and get 38w-36w-34w.

Our LED spotlight incorporates a COB BRIDGELUX CHIP diode with 2240 DS-C30 cores and achieves a very high light output.

With our commercial spotlight you can save up to 90% on your electricity bill.

Uses of the LED Spotlight 40W - 34W NEW MAYA White Single Phase Track - Professional Colour CRI+98 - UGR13

- Shop windows
- Offices
- Art galleries
- Museums

Notice: Product subject to change without prior notice. Ensure to use the most recent technical datasheet.

# Technical Datasheet

In FactorLED we ensure that our products have **QUALITY** guarantee and offer all the necessary elements for **DISTRIBUTION**, **IMPORT** or **WHOLESALE**, including the technical data sheet of each LED product.

## Additional images:

