


Linear Lamp Pendant - OSLO DOUBLE - 0.50m - 1m - 1.50m - 2m - IP20



Product code:

Reference: 13019

Technical specifications:

REFERENCE: 13019
Rated Power : 10W:0.5m - 20W: 1m - 30W: 1,5m - 40W: 2m
Nominal Voltage: 85V-265V
Colour: 2700K - 4000K - 6000K
CRI - Chromatic Rendiment Index: 90
Construction Material: Aluminium+PC
Luminosity-Lm: 1M:2000Lm / 2M: 4000Lm
Number & Type of LEDs: COB 384 Chips/M
Beam Angle (°): 120°
Luminous diode LED (Lm/W): 150Lm/W
Luminous Efficiency (Lm/W): 100 Lm/W
Certifications: CE - ROHS
IP : IP20
Diode Life Expectancy (H): 50.000
Dimensions (mm): L: 0,50m - 1,00m - 1,50m - 2,00m
Power Factor (PF): 0.97
Frequency (Hz): 50/60Hz
Temperature Range (°C): -20°C ~ +55°C
On/Off Cycles: 100.000
Starting Time (s): 0,2s
Glare Rating (UGR):
Energy Rating (2021-UE-2019/2015): A+
Energy Rating (2023 - UE-2019/2015): F
Warranty Years: 5

Product short description:

Our **Professional linear pendant luminaire 24V** - OSLO DOUBLE - is designed for intensive 24 hour uninterrupted use. Our surface mounted bar is manufactured in Europe, custom made to your requirements. Extruded aluminium of 98% purity, the professional light source is - DOUBLE COB 2 X 10W/M - delivers 384 chips / metre.

The integrated LED luminaire includes fixing clips, power supply included. 2 metres of cable. **5 years warranty. Lead time: 48h** (Monday to Friday).

Our diffuser is opal white.

Product description:

Linear Lamp Pendant - OSLO DOUBLE - IP20

Our LED linear is a versatile and timeless range, it can be the protagonist in the interior design of a space or adapt to it. Thanks to the different sizes and colours available, it can provide a wide variety of visual sensations that will define the space from a new perspective.

The **linear pendant - Double Oslo** - is designed for intensive professional use where a high quality of light - **CHROMATIC PERFORMANCE INDEX +90** - is required, as well as a good lifespan.

Available in various lengths to suit different needs and installation heights. The luminaires, up to 2 metres in length, become beautiful traces of light that shape the space.

Our linear pendant luminaire draws homogeneous lines of light that adapt to a variety of spaces with minimal visual impact, solving both general lighting needs and the floodlighting of vertical and horizontal planes.

Its design combines high transmittance diffusers that provide great visual comfort and energy efficiency.

Our **professional linear LED luminaire** has a power of 20W/metre (2x10W/M).

The light source of our linear LED luminaire **incorporates 2 x 10W COB strips** each with 384 high brightness chips/meter.

Our **integrated LED luminaire** is tailor-made for you, and offers a choice of warmer, neutral or cooler lighting and a variety of colours to choose from.

The luminaire is manufactured in Europe to the desired size of the customer, so this product does not allow product returns, as it is a custom-made product. Our manufacturing time is 48 working hours.

Uses of the Linear Lamp Pendant - OSLO DOUBLE - IP20

- Shops

Notice: Product subject to change without prior notice. Ensure to use the most recent technical datasheet.

Technical Datasheet

- Exhibitions
- Industries
- Offices
- Homes

In FactorLED we ensure that our products have QUALITY guarantee and offer all the necessary elements for DISTRIBUTION, IMPORT or WHOLESALE, including the technical data sheet of each LED product.

Additional images:

