

LED Spotlight 40W - 26W NEW MAYA White Three-Phase Rail - CCT - CRI+92 - UGR13 - HIGH LUMEN



Product code:

Reference: 90847-CCT

Technical specifications:

REFERENCE: 90847-CCT
Rated Power : 40w
Nominal Voltage: 85V-265V
Colour: 3000K - 4000K
CRI - Chromatic Rendiment Index: 92
Construction Material: Aluminium +PMMA
Luminosity-Lm: 4800
Number & Type of LEDs: COB BRIDGELUX 130 CHIP 2630 DS-C30
Beam Angle (°): Interchangeable angels: 24° - 60°
Luminous diodo LED (Lm/W): 120Lm/W
Luminous Efficiency (Lm/W): 120 Lm/W
Certifications: CE, CMIM, RoHS
Diode Life Expectancy (H): 30.000
Dimensions (mm): 160x80x156 mm
Power Factor (PF): 0.91
Frequency (Hz): 50/60Hz
Temperature Range (°C): 25°C ~ 45°C
On/Off Cycles: 100.000
Starting Time (s): 0,2s
Glare Rating (UGR): 13
Driver included: Driver No Flick
Energy Rating (2021-UE-2019/2015): A++
Energy Rating (2023 - UE-2019/2015): D
Warranty Years: 5

Product short description:

NEW MAYA LED track spotlight with adjustable power **40W - 38W - 36W - 34W - 32W - 30W - 28W - 26W** With professional colour rendering index **+92**- Professional and real colours -. It has 2 interchangeable light angles - 24° and 60° -. This makes this spotlight perfect for highlighting specific elements, thus creating multiple atmospheres. It does not produce glare UGR13.

Product description:

LED Spotlight 40W - 26W NEW MAYA White Three-Phase Rail - CCT - CRI+92 - UGR13 - HIGH LUMEN

Discover the versatility of the NEW MAYA LED Track Spot, a lighting solution that gives you total control over your lighting environment. Customise the Colour Temperature (CCT) and choose from preset wattages of **40W - 38W - 36W - 34W - 32W - 30W - 28W - 26W** to suit your specific needs. With an impressive CRI +98, this spotlight ensures vibrant and authentic colours, perfect for highlighting details and creating captivating environments.

This floodlight is equipped with a state-of-the-art PMMA hemispherical collimating lens and a curved diamond-shaped specular polished aluminium reflector. It offers a more concentrated base light and angle (24° primary and 60° secondary) to highlight objects without generating pronounced shadows.

Ideal for commercial environments, the floodlight includes a 60° reflector that widens the aperture angle, perfect for low ceilings or for highlighting larger objects.

With an impressive +98 CRI, our projector stands out for its exceptional colour rendering, displaying crisp, true-to-life colours.

Although the spotlight comes pre-set at 40W, the Driver cap allows you to adjust the power to 38W, 36W, 34W or 26W by dimming the output milliamps.

Glare reduction with a low UGR13 index ensures comfortable and professional illumination in any environment.

Equipped with a powerful COB BRIDGELUX CHIP diode with 2240 DS-C30 cores, our spotlight offers an extraordinary light output. In addition, the Driver with NO FLICK technology guarantees constant and flicker-free illumination.

Recommended applications:

Notice: Product subject to change without prior notice. Ensure to use the most recent technical datasheet.

Technical Datasheet

- Shop windows
- Office lighting
- Art galleries
- Museums

Discover the quality and versatility of the NEW MAYA LED Track Spotlight, designed to transform your spaces with style and efficiency.

In FactorLED we ensure that our products have QUALITY guarantee and offer all the necessary elements for DISTRIBUTION, IMPORT or WHOLESALE, including the technical data sheet of each LED product.

Additional images:

